

SAFETY DATA SHEET

Aquaseche

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Aquaseche

Product number 408-3

UFI: DDRV-01TC-Q00V-JQ03

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Rinse aid

Uses advised against For professional use only. This product is not recommended for any industrial, professional or

consumer use other than the Identified uses above.

1.3. Details of the supplier of the safety data sheet

Supplier Autosmart International Ltd

Lynn Lane

Shenstone, nr Lichfield Staffordshire. WS14 0DH

England

www.autosmartinternational.com

Tel: +44 (0) 1543 481616 (09:00 - 17:00)

SHREQ@autosmart.co.uk

Contact person Mr. Russell Butler

Manufacturer Autosmart International Ltd

Lynn Lane,

Shenstone, nr Lichfield Staffordshire. WS14 0DH

England

www.autosmartinternational.com

Tel: +44 (0) 1543 481616 (09:00 - 17:00) info@autosmartinternational.com

1.4. Emergency telephone number

Emergency telephone NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call

NCEC at +44 1865 407333 (24Hrs UK)

when calling please quote "AUTOSMART 29003-NCEC"

If you urgently need medical help or advice but it's not a life-threatening situation, call 111 free from any phone to speak to an NHS adviser. The 24-hour NHS 111 service can give you

healthcare advice or direct you to the local service that can help you best.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Aquaseche

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves, eye and face protection. P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention.

UFI: DDRV-01TC-Q00V-JQ03

Supplementary precautionary statements

P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/ container in accordance with local regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2-butoxyethanol 15<20%

CAS number: 111-76-2 EC number: 203-905-0

Substance with a Community workplace exposure limit.

Classification

Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

1-methoxy-2-propanol 5<10%

CAS number: 107-98-2 EC number: 203-539-1

Substance with National workplace exposure limits.

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336

Aquaseche

Maleic acid, Polymer with Diisobutene, sodium salt

3<5%

CAS number: 37199-81-8

Classification
Eye Irrit. 2 - H319

N,N-Didecyl-N,N-dimethylammonium carbonate (3:2)

0.2<0.5%

CAS number: 894406-76-9 EC number: 451-900-9

M factor (Acute) = 10

Classification

Acute Tox. 3 - H301 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Aquatic Acute 1 - H400 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

Skin contact Rinse with water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may

be inhaled, resulting in the same symptoms as inhalation.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.

6.2. Environmental precautions

Environmental precautions

Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Neutralise with acid. Caution. May generate heat. Following dilution and neutralisation, discharge to the sewer with plenty of water may be permitted. The requirements of the local water authority must be complied with if contaminated water is flushed directly to the sewer. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Store away from the following materials: Acids. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class

Acid-reactive storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

2-butoxyethanol

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³ Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³ Sk, BMGV

1-methoxy-2-propanol

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³ Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³ Sk

WEL = Workplace Exposure Limit. Sk = Can be absorbed through the skin. BMGV = Biological monitoring guidance value.

2-butoxyethanol (CAS: 111-76-2)

DNEL Industry - Dermal; Short term : 89 mg/kg/day

Industry - Inhalation; Short term: 246 mg/m³ Industry - Dermal; Long term: 75 mg/kg/day Industry - Inhalation; Long term: 98 mg/m³ Consumer - Dermal; Short term: 44.5 mg/kg/day Consumer - Inhalation; Short term: 123 mg/m³ Consumer - Oral; Short term: 13.4 mg/kg/day Consumer - Dermal; Long term: 38 mg/kg/day Consumer - Inhalation; Long term: 49 mg/m³

PNEC - Fresh water; 8.8 mg/l

- marine water; 0.88 mg/l

- Sediment (Freshwater); 8.14 mg/kg

Soil; 2.8 mg/kgSTP; 463 mg/l

Maleic acid, Polymer with Diisobutene, sodium salt (CAS: 37199-81-8)

Ingredient comments No exposure limits known for ingredient(s).

N,N-Didecyl-N,N-dimethylammonium carbonate (3:2) (CAS: 894406-76-9)

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment that provides appropriate eye and face protection should be worn. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Aquaseche

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body

protection

Appropriate footwear and additional protective clothing complying with an approved standard

should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures Provide eyewash station and safety shower. Contaminated work clothing should not be

allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried

out. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk

assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges suitable for intended use should be used. Full face mask respirators with replaceable filter cartridges suitable for intended use should be used. Half mask and quarter mask respirators with

replaceable filter cartridges suitable for intended use should be used.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Blue.

Odour Slight. Solvent.

pH pH (concentrated solution): 9.4

Melting point < -10°C

Initial boiling point and range 93°C

Flash point ~ 82°C Closed cup.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

No potentially hazardous reactions known.

Aquaseche

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time. Containers can burst violently or explode

when heated, due to excessive pressure build-up.

10.5. Incompatible materials

Materials to avoid Acid anhydrides. Acids. Phenols, cresols.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 7,680.25

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 7,051.28

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 70.51

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aquaseche

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may

be inhaled, resulting in the same symptoms as inhalation.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact Irritating to eyes.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

Toxicological information on ingredients.

2-butoxyethanol

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

1,300.0

Species Rat

ATE oral (mg/kg) 1,300.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,270.0

mg/kg)

Species

Rat

Acute toxicity - inhalation

ATE inhalation (vapours

ATE dermal (mg/kg)

mg/l)

11.0

1,100.0

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation:: Negative. This substance has no evidence of mutagenic

properties.

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity -

fertility

Fertility: - NOAEL 720 mg/kg, , Mouse

Reproductive toxicity -

development

Developmental toxicity: - NOAEL: 100 mg/kg, , Rat

Aquaseche

1-methoxy-2-propanol

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

5.660.0

Rat

Species

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 13,000.0

mg/kg)

Species Rabbit

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

N,N-Didecyl-N,N-dimethylammonium carbonate (3:2)

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

245.0

2,001.0

Species Rat

ATE oral (mg/kg) 245.0

Acute toxicity - dermal

Acute toxicity dermal (LD50

mg/kg)

Species Rat

ATE dermal (mg/kg) 2,001.0

Skin corrosion/irritation

Skin corrosion/irritation Corrosive to skin.

Animal data Dose: 50%, 4 hours, Rabbit

Skin sensitisation

Skin sensitisation - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Ames test: Negative. Chromosome aberration: Negative. Gene mutation: Negative.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 65 mg/kg, Oral,

SECTION 12: Ecological information

Not regarded as dangerous for the environment. However, large or frequent spills may have **Ecotoxicity**

hazardous effects on the environment.

Ecological information on ingredients.

Aquaseche

1-methoxy-2-propanol

Ecotoxicity The product components are not classified as environmentally hazardous.

However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met.

Ecological information on ingredients.

2-butoxyethanol

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: > 100 mg/l, Lepomis macrochirus (Bluegill)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 1550 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, >: > 100 mg/l,

Acute toxicity microorganisms EC₅₀, >: > 1000 mg/l,

Chronic aquatic toxicity

Chronic toxicity - fish early NOEC, 21 days: > 100 mg/l,

life stage

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 100 mg/l, Daphnia magna

1-methoxy-2-propanol

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: ~ 20800 mg/l,

N,N-Didecyl-N,N-dimethylammonium carbonate (3:2)

Acute aquatic toxicity

LE(C)50 $0.01 < L(E)C50 \le 0.1$

M factor (Acute) 10

LC₅₀, 96 hours: 0.28 mg/l, Lepomis macrochirus (Bluegill) Acute toxicity - fish

> LC₅₀, 96 hours: 1.1 mg/l, Cyprinodon variegatus (Sheepshead minnow) NOEC, 33 days: 0.018 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 0.066 mg/l, Daphnia magna

LC₅o, 96 hours: 0.073 mg/l, Freshwater invertebrates

NOEC, 21 days: 0.027 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

12.2. Persistence and degradability

EC₅₀, 96 hours: 0.025 mg/l, Freshwater algae

Acute toxicity -EC₅₀, 3 hours: 51 mg/l, Activated sludge

microorganisms

Persistence and degradability The degradability of the product is not known.

Aquaseche

Ecological information on ingredients.

2-butoxyethanol

Persistence and

degradability

The product is biodegradable.

Biodegradation

Water - Degradation (%) 90.4: 28 days

1-methoxy-2-propanol

Persistence and

degradability

Volatile substances are degraded in the atmosphere within a few days.

Maleic acid, Polymer with Diisobutene, sodium salt

Persistence and degradability

The product is degraded completely by abiotic oxidation.

N,N-Didecyl-N,N-dimethylammonium carbonate (3:2)

Persistence and degradability

The product is readily biodegradable. This surfactant complies with the

biodegradability criteria as laid down in The Detergents Regulations (as amended).

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

2-butoxyethanol

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient : 0.81

1-methoxy-2-propanol

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Maleic acid, Polymer with Diisobutene, sodium salt

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product is water-soluble and may spread in water systems. The product contains volatile

substances which may spread in the atmosphere.

Ecological information on ingredients.

2-butoxyethanol

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces.

Adsorption/desorption

coefficient

Water - Koc: ~ 67 @ °C

Henry's law constant 0.000016 atm m3/mol @ °C

Aquaseche

Surface tension 65 mN/m @ °C

1-methoxy-2-propanol

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces.

Maleic acid, Polymer with Diisobutene, sodium salt

Mobility The product contains substances which are bound to particulate matter and are

retained in soil.

N,N-Didecyl-N,N-dimethylammonium carbonate (3:2)

Mobility The product contains substances which are bound to particulate matter and are

retained in soil.

12.5. Results of PBT and vPvB assessment

Ecological information on ingredients.

2-butoxyethanol

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current UK criteria.

1-methoxy-2-propanol

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current UK criteria.

Maleic acid, Polymer with Diisobutene, sodium salt

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

SECTION 16: Other information

Aquaseche

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate.

LC50: Lethal Concentration to 50 % of a test population.

LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).

EC50: 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations

and acronyms

Eye Irrit. = Eye irritation Skin Irrit. = Skin irritation

General information This product has been manufactured under ISO 9001 and ISO 14001 Quality and

Environmental Management Systems.

Classification procedures according to SI 2019 No. 720

Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: : Calculation method.

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire,

WS14 0DH, Great Britain.

www.autosmartinternational.com

rbutler@autosmart.co.uk Tel +44 (0)1543 481616

Revision date 21/10/2019

Revision 3

Supersedes date 15/05/2018

SDS number 21215

SDS status Approved.

Hazard statements in full H226 Flammable liquid and vapour.

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Supersedes date: 15/05/2018

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.